

REXLiTE[®]

2021
ISSUE



MTOF 06
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 20° / 35° / 55°

Dimension (mm) : Ø50 × H67

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 400 / 424 / 434 / 444 Lm

Power Consumption : 6.1 W

Note : Open Ø46 mm



MTOE 16
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 20° / 35° / 50°

Dimension (mm) : Ø70 × H104

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50


CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,103 / 1,173 / 1,201 / 1,229 Lm

Power Consumption : 15.5 W

Note : Open Ø63 mm



MTOD 30
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 17° / 30° / 45°

Dimension (mm) : Ø111 x H147

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50


CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 2,375 / 2,526 / 2,586 / 2,646 Lm

Power Consumption : 31.1 W

Note : Open Ø103 mm



MTOD 30 W
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension (mm) : Ø111 x H147

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50


CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 2,375 / 2,526 / 2,586 / 2,646 Lm

Power Consumption : 31.1 W

Note : Open Ø103 mm



MTOD 30 TR
IP 20 / 44
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 17° / 30° / 45°

Dimension : Ø174 × H145 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,375 / 2,526 / 2,586 / 2,646 Lm

Power Consumption : 31.1 W

Note : Open Ø102 mm



MTOC 02 / 06 / 08
IP 20
REXMobius



Origin : Taiwan	Color Tolerance Adjustment : SDCM ≤ 3
Color : Black / White	Luminous Flux : 228 / 246 / 246 / 264 Lm
Beam Angle : 15° / 15° / 15°	543 / 543 / 586 / 586 Lm
Dimension: Ø33 × H60 mm	594 / 639 / 684 / 738 Lm
Ø33 × H85 mm	Power Consumption : 2.3 / 7.1 / 10 W
Ø33 × H111 mm	Note : Open Ø30 mm
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 60	
CCT : 2,700K / 3,000K / 4,000K / 5,000K	



MTUB 10
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø47 x H100 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 543 / 543 / 586 / 586 Lm

Power Consumption : 7.2 W

Note : Open Ø40 mm



MTOB 06 TR
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø120 × H115.5 mm

Light Source : COD LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 497 / 532 / 574 / 616 Lm

Power Consumption : 6.3 W

Note : Open Ø34 mm

REXMobius Series

09



MTOA 20
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø108 × H105 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø103 mm



MTBA 20
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : W185 × D158 × H128 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,061 / 2,144 / 2,175 / 2,176 / 2,597 Lm

Power Consumption : 20 W

Note : Open Ø170 X141 mm



MTBA 40
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : W298 × D185 × H128 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,061 / 2,144 / 2,175 / 2,176 / 2597 Lm

Power Consumption : 20 W

Note : Open Ø170 X 281 mm



MTYA 85 MA
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø196 × H140 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 7,503 / 7,818 / 7,924 / 7,938 / 9,470 Lm

Power Consumption : 85 W

Note : Open Ø183 mm

REXMobius Series

13



MTYA 10
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø113 × H120 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,020 / 1,062 / 1,076 / 1,078 / 1,285 Lm

Power Consumption : 10 W

Note : Open Ø104 mm

REXMobius Series

14



MTYA 20
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø160 × H135 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,062 / 2,144 / 2,175 / 2,176 / 2,597 Lm

Power Consumption : 20.5 W

Note : Open Ø143 mm

REXMobius Series

15



MTYA 35
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø196 × H133.5 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 35 W

Note : Open Ø183 mm



MTOB 02
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø33 x H60 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 213 / 228 / 246 / 264 Lm

Power Consumption : 2.5 W

Note : Open Ø30 mm



MTOB 02 W
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension : Ø33 x H66 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 213 / 228 / 246 / 264 Lm

Power Consumption : 2.5 W

Note : Open Ø30 mm



MTOB 06
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø33 x H85 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 497 / 532 / 574 / 616 Lm

Power Consumption : 6.3 W

Note : Open Ø30 mm

REXMobius Series

19



MTOB 06 W
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension : Ø33 x H91 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 645 / 690 / 743 / 744 Lm

Power Consumption : 6 W

Note : Open Ø30 mm



MTOB 06 T
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 24° / 38°

Dimension : Ø33 x H95 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 543 / 543 / 586 / 586 Lm

Power Consumption : 7.2 W

Note : Open Ø30 mm



MTOB 08
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 30° / 40°

Dimension : Ø33 x H111 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 533 / 570 / 615 / 660 Lm

Power Consumption : 7.8 W

Note : Open Ø30 mm



MTOB 08 W
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : Wallwash

Dimension : Ø33 x H117mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 60

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 533 / 570 / 615 / 660 Lm

Power Consumption : 7.8 W

Note : Open Ø30 mm

REXMobius Series

23



MTA 20 PL
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø99.5 × H118 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø91 mm



MTAA 20 AJPL
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø99.5 × H127 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø91 mm



MTAA 20 TR
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø155 × H118 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø91 mm



MTAA 20 AJ TR
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø89.5 × H127 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø91 mm

REXMobius Series

27



MTA 20
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø94 x H118 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø88 mm



MTA 20 AJ
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø94 x H127 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø88 mm



MTA 20 W
IP 20
REXMobius

REX LITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension : Ø94 x H118 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø88 mm



MTAA 20 WS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension : Ø108 × H86 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note : Open Ø90 mm



MTAB 30
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø136 × H120 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,797 / 2,907 / 2,950 / 2,952 / 3,523 Lm

Power Consumption : 28.4 W

Note : Open Ø130 mm



MTAB 30 AJ
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø136 × H129 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,797 / 2,907 / 2,950 / 2,952 / 3523 Lm

Power Consumption : 28.4 W

Note : Open Ø130 mm



MTAB 30 W
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : WallWash

Dimension : Ø136 × H120 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,797 / 2,907 / 2,950 / 2,952 / 3523 Lm

Power Consumption : 28 .4 W

Note : Open Ø130 mm



MTAC 17
IP 20 / 44
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø96 × H58 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,573 / 1,637 / 1,660 / 1,663 / 1,983 Lm

Power Consumption : 16.7 W

Note : Open Ø78 mm



MTAC 17T
IP 20 / 40
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø104 × H59.5 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,573 / 1,637 / 1,660 / 1,663 / 1,983 Lm

Power Consumption : 16.7 W

Note : Open Ø78 mm



MTAD 35
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 30° / 60°

Dimension : Ø116 × H82 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4 W

Note : Open Ø104 mm



MTAD 35V2
IP 20 / 44
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 30° / 60°

Dimension : Ø112 × H86.5 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4 W

Note : Open Ø104 mm



MTZA 12
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø76 x H71.5 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,209 / 1,258 / 1,275 / 1,278 / 1,523 Lm

Power Consumption : 12.2 W

Note : Open Ø64 mm



MTZA 12 T
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø92 x H75 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,209 / 1,258 / 1,275 / 1,278 / 1,523 Lm

Power Consumption : 12.2 W

Note : Open Ø64 mm



MTOG 12
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø103 × H100 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,209 / 1,258 / 1,275 / 1,278 / 1,523 Lm

Power Consumption : 12.2 W

Note : Open Ø96 mm



MTOG 122
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø103 × H100 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,209 / 1,258 / 1,275 / 1,278 / 1,523 Lm

Power Consumption : 12.2 W

Note : Open Ø96 mm



MTOG 123
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø103 × H100 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,209 / 1,258 / 1,275 / 1,278 / 1,523 Lm

Power Consumption : 12.2 W

Note : Open Ø96 mm



MTAE 20 Z
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° - 60°

Dimension : Ø62 x W70 x H233 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,367 / 1,453 / 1,488 / 1,522 Lm

Power Consumption : 19.8 W

Note :

REXMobius Series



MTEA 30
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan	Power Consumption : 31 W
Color : Black / White	Note :
Beam Angle : 15° / 25° / 40°	
Dimension : Ø80 x W70 x H220 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9	
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	
Luminous Flux : 3,000 / 3,119 / 3,164 / 3,166 / 3,778 Lm	



MTEA 40 D
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø64 x W150 x H220 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 4,054 / 4,216 / 4,277 / 4,280 / 5,107 Lm

Power Consumption : 45W

Note :



MTEA 25 H
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø80 x W228 x H225 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 2,816 / 2,928 / 2,971 / 2,973 / 3,547 Lm

Power Consumption : 28.8 W

Note :



MTEA 35 H
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø80 x W228 x H225 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 3,359 / 3,493 / 3,544 / 3,546 / 4,231 Lm

Power Consumption : 35.6W

Note :

REXMobius Series

48



MTUA 10
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 24° / 36°

Dimension : Ø36 x W166 x H118.5 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 822 / 874 / 894 / 915 Lm

Power Consumption : 10.7 W

Note :



MTUA 10 H
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 24° / 36°

Dimension : Ø36 x W162 x H143 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 3,500K / 4,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 822 / 874 / 894 / 915 Lm

Power Consumption : 10.7 W

Note :



MTRB 5
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø52 x W70 x H120 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 480 / 495 / 510 / 510 Lm

Power Consumption : 5 W

Note :



MTRB 7
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø52 x W70 x H120 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 625 / 635 / 660 / 660 Lm

Power Consumption : 7 W

Note :



MTRB 10
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan	Power Consumption : 10 W
Color : Black / White	Note :
Beam Angle : 15° / 25° / 40°	
Dimension : Ø52 x W70 x H120 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50	
CCT : 2,700K / 3,000K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	
Luminous Flux : 955 / 980 / 1,015 / 1,015 Lm	



MTRA 15 / MTRA 15 PLUS
IP 20
REXMobius



Origin : Taiwan	Luminous Flux : 1,407 / 1,470 / 1,508 / 1,514 / 1,860 Lm
Color : Black / White	Power Consumption : 14.9 W
Beam Angle : 15° / 25° / 40° / 60°	Note :
Dimension: Ø52 × W70 × H195 mm	
Ø52 × W70 × H202 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9	
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	



MTRA 15 H / MTRA 15 H PLUS
IP 20
REXMobius

REX[®]LITE
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø52 × W162 × H138 mm

Ø52 × W162 × H145 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,393 / 1,450 / 1,470 / 1,473 / 1,756 Lm

Power Consumption : 14.4 W

Note :



MTRA 25 H / MTRA 25 H PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø52 x W162 x H198 mm

Ø52 x W162 x H205 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,254 / 2,346 / 2,378 / 2,383 / 2,840 Lm

Power Consumption : 26.1 W

Note :



MTRA 15 D / MTRA 15 D PLUS
IP 20
REXMobius

REX[®]LiTE
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø52 x W150 x H135 mm

Ø52 x W150 x H142 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9


CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,393 / 1,450 / 1,470 / 1,473 / 1,756 Lm

Power Consumption : 14.4 W

Note :



MTRA 25W D / MTRA 25W D PLUS
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°v

Dimension : Ø52 × W150 × H195 mm

Ø52 × W150 × H202 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,254 / 2,346 / 2,378 / 2,383 / 2,840 Lm

Power Consumption : 26.1 W

Note :



MTAF 14
IP 20
REXMobius

REX[®]LITE
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø62 x W70 x H125 mm

Light Source : COB LED AEEAY

LED Specs : Ra ≥ 90 R9 ≥ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,245 / 1,280 / 1,330 / 1,330 Lm

Power Consumption : 14W

Note :



MTAE 20 / MTAE 20 PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan	Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm
Color : Black / White	Power Consumption : 23.3 W
Beam Angle : 15° / 25° / 40° / 60°	Note :
Dimension : Ø62 × W70 × H200 mm	
Ø62 × W70 × H207 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9	
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	



MTAE 17 H / MTAE 17 H PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W162 x H133 mm

Ø62 x W162 x H140 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,749 / 1,821 / 1,846 / 1,849 / 2,204 Lm

Power Consumption : 19 W

Note :



MTAE 25H / MTAE 25 H PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W162 x H163 mm

Ø62 x W162 x H170 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,572 / 2,678 / 2,714 / 2,720 / 3,242 Lm

Power Consumption : 31.1 W

Note :



MTAE 32 H / MTAE 32 H PLUS
IP 20
REXMobius

REX[®]LiTE
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 55°

Dimension : Ø62 × W228 × H203 mm

Ø62 × W228 × H210 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4 W

Note :



MTAE 17 D / MTAE 17 D PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W150 x H130 mm

Ø62 x W150 x H137 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,749 / 1,821 / 1,846 / 1,849 / 2,204 Lm

Power Consumption : 19 W

Note :



MTAE 25 D / MTAE 25 D PLUS
IP 20
REXMobius

REX[®]LiTE
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W150 x H160 mm

Ø62 x W150 x H167 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,572 / 2,678 / 2,714 / 2,720 / 3,242 Lm

Power Consumption : 31.1 W

Note :



MTAE 32 D / MTEA 32 D PLUS
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø62 x W150 x H200 mm

Ø62 x W150 x H197 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4 W

Note :

REXMobius Series

66



MTRC 25
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 30° / 60°

Dimension : Ø86 x H153 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,797 / 2,907 / 2,950 / 2,952 / 3,523 Lm

Power Consumption : 29.6 W

Note :



MTRC 30
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 30° / 60°

Dimension : Ø86 x H153 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4 W

Note :

REXMobius Series

68



MTRD 10
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø122 × H165 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,020 / 1,062 / 1,076 / 1,278 / 1,285 Lm

Power Consumption : 12.2 W

Note :

REXMobius Series

69



MTRD 20
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø122 × H165 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note :

REXMobius Series

70



MTIA 20
IP 65
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø150 × H180 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 2,062 / 2,144 / 2,175 / 2,176 / 2,597 Lm

Power Consumption : 20.5 W

Note :



MTIA 30
IP 65
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø150 × H180 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,148 / 3,272 / 3,321 / 3,322 / 3,965 Lm

Power Consumption : 34.4W

Note :



MTIA 40
IP 65
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 40° / 60°

Dimension : Ø150 × H180 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 3,982 / 4,139 / 4,200 / 4,202 / 5,016 Lm

Power Consumption : 46.6 W

Note :

REXMobius Series



MTRB 5S / 7S / 10S
IP 20
REXMobius



Origin : Taiwan	Luminous Flux : 480 / 495 / 510 / 510 Lm
Color : Black / White	625 / 635 / 660 / 660 Lm
Beam Angle : 15° / 25° / 40°	955 / 980 / 1015 / 1015 Lm
Dimension : Ø52 × H80 mm	Power Consumption : 5 / 7 / 10 W
Light Source : COB LED ARRAY	Note :
LED Specs : Ra ≥ 90 R9 ≥ 50	
CCT : 2,700K / 3,000K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	

REXMobius Series



MTRB 5T / 7T / 10T
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan	Luminous Flux : 480 / 495 / 510 / 510 Lm
Color : Black / White	625 / 635 / 660 / 660 Lm
Beam Angle : 15° / 25° / 40°	955 / 980 / 1015 / 1015 Lm
Dimension : Ø52 x W100 x H100 mm	Power Consumption : 5 / 7 / 10 W
Light Source : COB LED ARRAY	Note :
LED Specs : Ra ≥ 90 R9 ≥ 50	
CCT : 2,700K / 3,000K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	

REXMobius Series

75



MTRB 5P / 7P / 10P
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan	Luminous Flux : 480 / 495 / 510 / 510 Lm
Color : Black / White	625 / 635 / 660 / 660 Lm
Beam Angle : 15° / 25° / 40°	955 / 980 / 1015 / 1015 Lm
Dimension : Ø52 x W100 x H1100 mm	Power Consumption : 5 / 7 / 10 W
Light Source : COB LED ARRAY	Note :
LED Specs : Ra ≥ 90 R9 ≥ 50	
CCT : 2,700K / 3,000K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	

REXMobius Series



MTRA 15 S
IP 20
REXMobius



Origin : Taiwan
Color : Black / White
Beam Angle : 15° / 25° / 40° / 60°
Dimension : Ø52 x H155 mm
Light Source : COB LED ARRAY
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Color Tolerance Adjustment : SDCM ≤ 3
Luminous Flux : 1,407 / 1,470 / 1,508 / 1,514 / 1,860 Lm

Power Consumption : 14.9 W
Note :

REXMobius Series

77



MTRA 15 T
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø52 x W100 x H175 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,407 / 1,470 / 1,508 / 1,514 / 1,860 Lm

Power Consumption : 14.9 W

Note :



MTRA 15 P
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø52 x W100 x H1175 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50 , 5,000K : Ra $\geq$ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,407 / 1,470 / 1,508 / 1,514 / 1,860 Lm

Power Consumption : 14.9 W

Note :

REXMobius Series

79



MTAF 14 S
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension: Ø62 × H85 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,245 / 1,280 / 1,330 / 1,330 Lm

Power Consumption : 13.8 W

Note :

REXMobius Series

80



MTAF 14 T
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø62 x W100 x H105 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,245 / 1,280 / 1,330 / 1,330 Lm

Power Consumption : 13.8 W

Note :

REXMobius Series

81



MTAE 14 P
IP 20
REXMobius

REXLITE®
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40°

Dimension : Ø62 x W100 x H1105 mm

Light Source : COB LED ARRAY

LED Specs : Ra $\geq$ 90 R9 $\geq$ 50

CCT : 2,700K / 3,000K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM $\leq$ 3

Luminous Flux : 1,245 / 1,280 / 1,330 / 1,330 Lm

Power Consumption : 13.8 W

Note :

REXMobius Series



MTAE 20 S
IP 20
REXMobius



Origin : Taiwan	Power Consumption : 21.3 W
Color : Black / White	Note :
Beam Angle : 15° / 25° / 40° / 60°	
Dimension : Ø62 x H160 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9	
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	
Luminous Flux: 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm	

REXMobius Series

83



MTAE 20 T
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W100 x H180 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note :

REXMobius Series

84



MTAE 20 P
IP 20
REXMobius

REXLITE[®]
瑞司照明系統

Origin : Taiwan

Color : Black / White

Beam Angle : 15° / 25° / 40° / 60°

Dimension : Ø62 x W100 x H1180 mm

Light Source : COB LED ARRAY

LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9

CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K

Color Tolerance Adjustment : SDCM ≤ 3

Luminous Flux : 1,921 / 2,000 / 2,027 / 2,031 / 2,421 Lm

Power Consumption : 21.3 W

Note :



MTRA 13 LV / MTRA 13 LV PLUS
IP 20
REXMobius

REX[®]LiTE
瑞司照明系統

Origin : Taiwan	Luminous Flux : 1,393 / 1,450 / 1,470 / 1,473 / 1,756 Lm
Color : Black / White	Power Consumption : 14.4 W
Beam Angle : 15° / 25° / 40°	Note :
Dimension : Ø52 x W70 x H139 mm	
Ø52 x W70 x H146 mm	
Light Source : COB LED ARRAY	
LED Specs : Ra ≥ 90 R9 ≥ 50 , 5,000K : Ra ≥ 80 R9	
CCT : 2,700K / 3,000K / 3,500K / 4,000K / 5,000K	
Color Tolerance Adjustment : SDCM ≤ 3	

REX Lite®
瑞司照明系統

FISHBONE Design

觀境設計股份有限公司



REX Lite®



CASAMBI

TCI

GLOBAL

ZUSU

techno

STEAB

PANDUL

412027 台中市大里區
西湖路187巷108號 | 總公司
No.108, Ln.187, Xihu Rd., Dali Dist.,
Taichung City 412027, Taiwan | Headquarter

408008 台中市南屯區
文心南路39號 | 品牌意識空間
No. 39, Wenxin S. Rd., Nantun Dist.,
Taichung City 408008, Taiwan

106022 台北市大安區
建國南路二段69巷56號 | 設計師聚會所
No.56, Ln. 69, Sec. 2, Jianguo S. Rd., Da'an Dist.,
Taipei City 106022, Taiwan

T +886-4-2496-4053

F +886-4-2496-0497

W www.rexlite.com.tw

f REXLITE

@ rexlite.tw

客服專線 TEL 0800-279-979